



**Note:** This IBM PC BIOS API call is for DOS/Win16 personality only. Use [Family API](#) for portability.

**Note:** [osFree Macro Library](#) provides macros for most of functions

2022/03/13 05:41 · prokushev · [0 Comments](#)

# Int 13H, AH=02H

## Version

IBM 5150 and higher

## Brief

Read sector

## Family API

[DosRead](#)

## Input

- AH = 02h
- AL = number of sectors to read (must be nonzero)
- CH = low eight bits of cylinder number
- CL = sector number 1-63 (bits 0-5) high two bits of cylinder (bits 6-7, hard disk only)
- DH = head number
- DL = drive number (bit 7 set for hard disk)
- ES:BX → data buffer

## Return

- CF set on error
  - if AH = 11h (corrected ECC error), AL = burst length
- CF clear if successful
- AH = status (see #00234)
- AL = number of sectors transferred (only valid if CF set for some BIOSes)

## Macro

```
INCLUDE BIOS.INC

@DskRead 0, 0, 0, 1, 1, offset buf
```

## Notes

- errors on a floppy may be due to the motor failing to spin up quickly enough; the read should be retried at least three times, resetting the disk with AH=00h between attempts
- most BIOSes support “multitrack” reads, where the value in AL exceeds the number of sectors remaining on the track, in which case any additional sectors are read beginning at sector 1 on the following head in the same cylinder; the MSDOS CONFIG.SYS command MULTITRACK (or the Novell DOS DEBLOCK=) can be used to force DOS to split disk accesses which would wrap across a track boundary into two separate calls
- the IBM AT BIOS and many other BIOSes use only the low four bits of DH (head number) since the WD-1003 controller which is the standard AT controller (and the controller that IDE emulates) only supports 16 heads
- AWARD AT BIOS and AMI 386sx BIOS have been extended to handle more than 1024 cylinders by placing bits 10 and 11 of the cylinder number into bits 6 and 7 of DH
- under Windows95, a volume must be locked (see INT 21/AX=440Dh/CX=084Bh) in order to perform direct accesses such as INT 13h reads and writes
- all versions of MS-DOS (including MS-DOS 7 [Windows 95]) have a bug which prevents booting on hard disks with 256 heads (FFh), so many modern BIOSes provide mappings with at most 255 (FEh) heads
- some cache drivers flush their buffers when detecting that DOS is bypassed by directly issuing INT 13h from applications. A dummy read can be used as one of several methods to force cache flushing for unknown caches (e.g. before rebooting).
- When reading from floppies, some AMI BIOSes (around 1990-1991) trash the byte following the data buffer, if it is not arranged to an even memory boundary. A workaround is to either make the buffer word aligned (which may also help to speed up things), or to add a dummy byte after the buffer.
- MS-DOS may leave interrupts disabled on return from this function.
- Apparently some BIOSes or intercepting resident software have bugs that may destroy DX on return or not properly set the Carry flag. At least some Microsoft software frames calls to this function with PUSH DX, STC, INT 13h, STI, POP DX.
- on the original IBM AT BIOS (1984/01/10) this function does not disable interrupts for harddisks (DL >= 80h). On these machines the MS-DOS/PC DOS IO.SYS/IBMBIO.COM installs a special filter to bypass the buggy code in the ROM (see CALL F000h:211Eh)

## Note

Text based on [Ralf Brown Interrupt List Release 61](#)

<b>IBM PC BIOS API</b>	
Video I/O	<b>INT 10H:</b> 00H, 01H, 02H, 03H, 05H, 06H, 07H, 08H, 09H, 0AH, 0BH, 0CH, 0DH, 0EH, 0FH
Hardware info	<b>INT 11H, INT 12H</b>
Serial I/O	<b>INT 14H:</b> 00H, 01H, 02H, 03H
Tape I/O	<b>INT 15H:</b> 00H, 01H, 02H, 03H
Keyboard I/O	<b>INT 16H:</b> 00H, 01H, 02H
Printer I/O	<b>INT 17H:</b> 00H, 01H, 02H
Disk I/O	<b>INT 13H:</b> 00H, 01H, 02H, 03H, 04H, 05H
Date and Time	<b>INT 1AH:</b> 00H, 01H

<b>osFree Macro Library</b>	
Video I/O	@SetMode @SetCurSz @SetCurPos @GetCur @SetPage @ScrollUp @ScrollDn @Scroll @GetChAtr @PutChAtr @PutCh @SetPalet @SetColor @SetDot @GetDot @WrtTTY @VideoState @GetMode @GetDisplay @GetVideoState @GetEGAIInfo @CIs
Hardware info	@Equipment @MemSize
Serial I/O	@AuxInit @AuxSendChar @AuxRecieveChar @AuxStatus
Tape I/O	@TapeOn @TapeOff @TapeRead @TapeWrite
Keyboard I/O	@KbdStatus @CharIn @CharPeek
Printer I/O	@PrnPrint @PrnInit @PrnStatus
Disk I/O	@DskReset @DskStatus @DskRead @DskWrite @DskVerify @DskFormat
Date and Time	@SetTime @GetTime
Mouse	@MouInit @MouShowPointer @MouStatus @MouSetPos @MouSetMickey @MouRegion
Memory manager	@ModBlok SET_BLOCK

2022/10/04 14:28 · prokushev · 0 Comments

2022/03/13 05:54 · prokushev · 0 Comments

<b>Family API</b>	
DOS	Process Manager DosBeep DosExit DosSleep DosExecPgm
	File Manager DosChDir DosChgFilePtr DosClose DosDelete DosDupHandle DosMkDir DosMove DosQCurDir DosQCurDisk DosSet FileMode DosOpen DosQFileInfo DosRead DosQ FileMode DosQFSInfo DosQVerify DosRmDir DosSelectDisk DosFindClose DosFindFirst DosFindNext DosSet FileInfo DosSet Verify DosWrite DosFileLocks DosSet FHand State DosNewSize DosBufReset DosQFHand State DosSet FSinfo
	Memory Manager DosFreeSeg DosSubAlloc DosSubFree DosSubSet DosAlloc Huge DosAlloc Seg DosRealloc Huge DosRealloc Seg DosGet Huge Shift DosCreate CS Alias
	NLS DosCaseMap DosGet Ctry Info DosGet DBCSEv DosSet Ctry Code DosGet Collate DosGet Message DosIns Message DosPut Message
	Date and Time DosSet Date Time DosGet Date Time
	Devices DosDevConfig DosDevIOCtl DosDevIOCtl2
	Signals DosHold Signal DosSet Sig Handler
	Misc BadDynLink DosGet Env DosGet Machine Mode DosGet Version DosError DosErr Class DosSet Vec
KBD	KbdCharIn KbdFlushBuffer KbdGet Status KbdSet Status KbdStringIn KbdPeek

## Family API

VIO	<a href="#">VioGetBuf</a> <a href="#">VioGetConfig</a> <a href="#">VioGetCurPos</a> <a href="#">VioGetCurType</a> <a href="#">VioGetPhysBuf</a> <a href="#">VioReadCellStr</a> <a href="#">VioReadCharStr</a> <a href="#">VioScrollUp</a> <a href="#">VioScrollDn</a> <a href="#">VioScrollLf</a> <a href="#">VioScrollRt</a> <a href="#">VioScrUnLock</a> <a href="#">VioSetCurPos</a> <a href="#">VioSetCurType</a> <a href="#">VioSetMode</a> <a href="#">VioGetMode</a> <a href="#">VioShowBuf</a> <a href="#">VioWrtCellStr</a> <a href="#">VioWrtCharStr</a> <a href="#">VioWrtCharStrAtt</a> <a href="#">VioWrtNAttr</a> <a href="#">VioWrtNCell</a> <a href="#">VioWrtNChar</a> <a href="#">VioWrtTTY</a> <a href="#">VioScrLock</a> <a href="#">VioPopUp</a>
Tools	BIND
Modules	<a href="#">DOSCALLS.DLL</a> <a href="#">VIOCALLS.DLL</a> <a href="#">KBDCALLS.DLL</a> <a href="#">MSG.DLL</a>
Libraries	<a href="#">API.LIB</a> <a href="#">OS2386.LIB</a> <a href="#">FAPI.LIB</a> <a href="#">DOSCALLS.LIB</a> <a href="#">SUBCALLS.LIB</a>

2018/08/25 15:05 · prokushev · [0 Comments](#)

From:  
<http://ftp.osfree.org/doku/> - osFree wiki



Permanent link:  
<http://ftp.osfree.org/doku/doku.php?id=en:docs:bios:api:int13:02&rev=1648375857>

Last update: **2022/03/27 10:10**