



This is part of **Family API** which allow to create dual-os version of program runs under OS/2 and DOS

Note: This is legacy API call. It is recommended to use 32-bit equivalent

2021/09/17 04:47 · prokushhev · [0 Comments](#)

2021/08/20 03:18 · prokushhev · [0 Comments](#)

KbdCharIn

This call returns a character data record from the keyboard.

Syntax

KbdCharIn (CharData, IOWait, KbdHandle)

Parameters

:CharData (PKBDKEYINFO) - output : Address of the character data structure: :asciicharcode (UCHAR) : ASCII character code. The scan code received from the keyboard is translated to the ASCII character code. :scancode (UCHAR) : Code received from the keyboard. The scan code received from the keyboard is translated to the ASCII character code.

status (UCHAR) : State of the keystroke event: 'Bit Description' 7-6 00 = Undefined

```
01 = Final character, interim character flag off
10 = Interim character
11 = Final character, interim character flag on.
```

5 1 = Immediate conversion requested.

4-2 Reserved.

1 0 = Scan code is a character.

```
1 = Scan code is not a character; is an extended key code from the
keyboard.
```

0 1 = Shift status returned without character. reserved (UCHAR):NLS shift status. Reserved, set to zero. 7 Kana-To-Kanji Conversion Mode (Japanese)

```
Hanja_25: Hangeul-to-Hanja Conversion Mode (Korean)
Reserved (T-Chinese)
```

6 Romaji Mode (Japanese)

Hanja_CSR: Hangeul-to-Hanja Conversion Mode (Korean) Reserved (T-Chinese)

5 Reserved 4-3

```
00 Shift Indicator Row always visible  
01 Shift Indicator Row always invisible  
10 Shift Indicator Row visible only when a shift key is pressed.  
    And it becomes invisible, depress another key.  
11 Reserved
```

2-1

```
00 Alphanumeric Mode  
01 Katakana Mode (Japanese)  
    Jamo Mode (Korean)  
    Phonetic Input Mode (T-Chinese)  
10 Hiragana Mode (Japanese)  
    Hangeul Mode (Korean)  
    TsangJye Input Mode (T-Chinese)  
11 Reserved
```

0 DBCS Mode

shiftkeystat (USHORT) : Shift key status. 'Bit Description' 15 SysReq key down 14 CapsLock key down 13 NumLock key down 12 ScrollLock key down 11 Right Alt key down (SBCS) 10 Right Ctrl key down (SBCS) 9 Left Alt key down 8 Left Ctrl key down 7 Insert on 6 CapsLock on 5 NumLock on 4 ScrollLock on 3 Either Alt key down (DBCS) 2 Either Ctrl key down (DBCS) 1 Left Shift key down 0 Right Shift key down time (ULONG) : Time stamp indicating when a key was pressed. It is specified in milliseconds from the time the system was started.

;IOWait (USHORT) - input : Wait if a character is not available. 'Value Definition' 0 Requestor waits for a character if one is not available. 1 Requestor gets an immediate return if no character is available. ;KbdHandle (HKBD) - input : Default keyboard or the logical keyboard.

Return Code

rc (USHORT) - return Return code descriptions are:
* 0 NO_ERROR * 375 ERROR_KBD_INVALID_IOWAIT
* 439 ERROR_KBD_INVALID_HANDLE * 445 ERROR_KBD_FOCUS_REQUIRED * 447
ERROR_KBD_KEYBOARD_BUSY * 464 ERROR_KBD_DETACHED * 504 ERROR_KBD_EXTENDED_SG

Remarks

On an enhanced keyboard, the secondary enter key returns the normal character 0DH and a scan code of E0H.

Double-byte character codes (DBCS) require two function calls to obtain the entire code.

If shift report is set with KbdSetStatus, the CharData record returned reflects changed shift information only.

Extended ASCII codes are identified with the status byte, bit 1 on and the ASCII character code being either 00H or E0H. Both conditions must be satisfied for the character to be an extended keystroke. For extended ASCII codes, the scan code byte returned is the second code (extended code). Usually the extended ASCII code is the scan code of the primary key that was pressed.

A thread in the foreground session that repeatedly polls the keyboard with KbdCharIn (with no wait), can prevent all regular priority class threads from executing. If polling must be used and a minimal amount of other processing is being performed, the thread should periodically yield to the CPU by issuing a DosSleep call for an interval of at least 5 milliseconds.

Family API Considerations

Some options operate differently in the DOS mode than in the OS /2 mode. Therefore, the following restrictions apply to KbdCharIn when coding in the DOS mode:

- * The CharData structure includes everything except the time stamp.
- * Interim character is not supported
- * Status can be 0 or 40H
- * KbdHandle is ignored.

Example Code

C Binding

```
<PRE> typedef struct _KBDKEYINFO { /* kbc */  
  
    UCHAR    chChar;           /* ASCII character code */  
    UCHAR    chScan;          /* Scan Code */  
    UCHAR    fbStatus;        /* State of the character */  
    UCHAR    bNlsShift;       /* Reserved (set to zero) */  
    USHORT   fsState;         /* State of the shift keys */  
    ULONG    time;            /* Time stamp of keystroke (ms since ipl) */  
  
}KBDKEYINFO;  
  
#define INCL_KBD  
  
USHORT rc = KbdCharIn(CharData, IOWait, KbdHandle);  
  
PKBDKEYINFO CharData; /* Buffer for data */ USHORT IOWait; /* Indicate if wait */ HKBD KbdHandle; /*  
Keyboard handle */  
  
USHORT rc; /* return code */ </PRE>
```

MASM Binding

```
<PRE> KBDKEYINFO struc
```

```

kbcI_chChar    db ? ;ASCII character code
kbcI_chScan    db ? ;Scan Code
kbcI_fbStatus  db ? ;State of the character
kbcI_bNlsShift db ? ;Reserved (set to zero)
kbcI_fsState   dw ? ;state of the shift keys
kbcI_time      dd ? ;time stamp of keystroke (ms since ipl)

```

KBDKEYINFO ends

EXTRN KbdCharIn:FAR INCL_KBD EQU 1

PUSH@ OTHER CharData ;Buffer for data PUSH WORD IOWait ;Indicate if wait PUSH WORD KbdHandle
;Keyboard handle CALL KbdCharIn

Returns WORD </PRE>

Note

Text based on [http://www.edm2.com/index.php/KbdCharIn_\(FAPI\)](http://www.edm2.com/index.php/KbdCharIn_(FAPI))

Family API	
DOS	Process Manager DosBeep DosExit DosSleep DosExecPgm
	File Manager DosChDir DosChgFilePtr DosClose DosDelete DosDupHandle DosMkDir DosMove DosQCurDir DosQCurDisk DosSet FileMode DosOpen DosQFileInfo DosRead DosQFileInfo DosQFSInfo DosQVerify DosRmDir DosSelectDisk DosFindClose DosFindFirst DosFindNext DosSet FileInfo DosSet Verify DosWrite DosFileLocks DosSetFHandState DosNewSize DosBufReset DosQFHandState DosSetFSinfo
	Memory Manager DosFreeSeg DosSubAlloc DosSubFree DosSubSet DosAllocHuge DosAllocSeg DosReallocHuge DosReallocSeg DosGetHugeShift DosCreateCSAlias
	NLS DosCaseMap DosGetCtryInfo DosGetDBCSEv DosSetCtryCode DosGetCollate DosGetMessage DosInsMessage DosPutMessage
	Date and Time DosSetDateTime DosGetDateTime
	Devices DosDevConfig DosDevIOCtl DosDevIOCtl2
	Signals DosHoldSignal DosSetSigHandler
	Misc BadDynLink DosGetEnv DosGetMachineMode DosGetVersion DosError DosErrClass DosSetVec
KBD KbdCharIn KbdFlushBuffer KbdGetStatus KbdSetStatus KbdStringIn KbdPeek	
VIO VioGetBuf VioGetConfig VioGetCurPos VioGetCurType VioGetPhysBuf VioReadCellStr VioReadCharStr VioScrollUp VioScrollDn VioScrollLf VioScrollRt VioScrUnLock VioSetCurPos VioSetCurType VioSetMode VioGetMode VioShowBuf VioWrtCellStr VioWrtCharStr VioWrtCharStrAtt VioWrtNAttr VioWrtNCell VioWrtNChar VioWrtTTY VioScrLock VioPopUp	
Tools	BIND
Modules	DOSCALLS.DLL VIOCALLS.DLL KBDCALLS.DLL MSG.DLL
Libraries	API.LIB OS2386.LIB FAPI.LIB DOSCALLS.LIB SUBCALLS.LIB

2018/08/25 15:05 · prokushev · 0 Comments

From:
<http://ftp.osfree.org/doku/> - osFree wiki



Permanent link:
<http://ftp.osfree.org/doku/doku.php?id=en:docs:fapi:kbdcharin&rev=1629446209>

Last update: **2021/08/20 07:56**