

MouOpen

Bindings: C, MASM

This call opens the mouse device for the current session.

MouOpen (DriverName, DeviceHandle)

DriverName (PSZ) - input *DriverName* is a far pointer to an **ASCIIZ** string in application storage containing the name of the pointer draw device driver to be used as the pointer-image drawing routine for this session.

The name of the device driver must be included in the **CONFIG.SYS** file at system start-up time. Applications that use the default pointer draw device driver supplied by the system must push a double-word of 0s in place of an address.

DriverName has a different definition when the caller is the Base Video Subsystem (**BVS**). In this case the selector portion of the far address is zero. The offset portion is non-zero and contains a display configuration number (sequentially numbered where 1 is the first display configuration). The *MouOpen* call issued by **BVS** is executed on the [VioSetMode](#) path. Using the display configuration number passed on the *MouOpen* call, the Base Mouse Subsystem can detect a change in display configurations. This form of the *MouOpen* call is not recommended for applications. Applications should either push the far address of an **ASCIIZ** pointer draw device driver name or push two words of zeros.

DeviceHandle (PHMOU) - output Address of a 1-word value that represents the mouse handle returned to the application.

rc (USHORT) - return Return code descriptions are:

0	NO_ERROR
385	ERROR_MOUSE_NO_DEVICE
390	ERROR_MOUSE_INV_MODULE_PT
466	ERROR_MOU_DETACHED
501	ERROR_MOUSE_NO_CONSOLE
505	ERROR_MOU_EXTENDED_SG

Remarks

MouOpen initializes the Mouse functions to a known state. The application may have to issue additional mouse functions to establish the environment it desires. For example, after the *MouOpen*, the collision area is defined to be the size of the entire display. Therefore, to get the pointer to be displayed, the application must issue a *MouDrawPtr* to remove the collision area.

The state of the mouse after the first *MouOpen* is:

- Row/Col scale factors set to 16/8. (See [MouSetScaleFact](#).)
- All events reported. (See [MouSetEventMask](#).)
- Empty event queue. (See [MouReadEventQue](#) and [MouGetNumQueEl](#).)
- All user settable Device Status bits reset. (Set to zero. See [MouSetDevStatus](#).)
- Pointer set to center of screen if valid display mode is set. (See [MouSetPtrPos](#).)

- Pointer shape set to the default for the pointer device driver currently registered in the session. (See [MouSetPtrShape](#).)
- Collision area equal to full screen. (See [MouDrawPtr](#) and [MouRemovePtr](#).)

C bindings

```
#define INCL_MOU

USHORT rc = MouOpen(DriverName, DeviceHandle);

PSZ DriverName; /* Pointer draw driver name */
PHMOU DeviceHandle; /* Mouse device handle */

USHORT rc; /* return code */
```

MASM bindings

```
EXTRN MouOpen:FAR
INCL_MOU EQU 1

PUSH@ ASCIIZ DriverName ;Pointer draw driver name
PUSH@ WORD DeviceHandle ;Mouse device handle
CALL MouOpen

Returns WORD
```

From:
<http://ftp.osfree.org/doku/> - osFree wiki

Permanent link:
<http://ftp.osfree.org/doku/doku.php?id=en:ibm:prcp:mou:open>

Last update: **2016/09/15 04:13**

