

VioGetAnsi

Bindings: C, MASM

This call returns the current ANSI status On/Off state.

VioGetAnsi (Indicator, VioHandle)

Indicator (**PUSHORT**) - output Address of the current ANSI status. A value of 1 indicates ANSI is active, and a value of 0 indicates ANSI is not active.

VioHandle (**HVIO**) - input This must be zero unless the caller is a Presentation Manager application, in which case it must be the value returned by [VioGetPs](#).

rc (**USHORT**) - return Return code descriptions are:

0	NO_ERROR
436	ERROR_VIO_INVALID_HANDLE
465	ERROR_VIO_DETACHED

C bindings

```
#define INCL_VIO

USHORT rc = VioGetAnsi(Indicator, VioHandle);

PUSHORT      Indicator;      /* On/Off indicator (returned) */
HVIO          VioHandle;     /* Vio handle */

USHORT        rc;            /* return code */
```

MASM bindings

```
EXTRN VioGetAnsi:FAR
INCL_VIO EQU 1

PUSH@ WORD Indicator ;On/Off indicator (returned)
PUSH WORD VioHandle ;Vio handle
CALL VioGetAnsi
```

Returns **WORD**

From:
<http://ftp.osfree.org/doku/> - osFree wiki

Permanent link:
<http://ftp.osfree.org/doku/doku.php?id=en:ibm:prcp:vio:getansi>

Last update: 2016/09/14 10:53



