



This is part of **Family API** which allow to create dual-os version of program runs under OS/2 and DOS

**Note:** This is legacy API call. It is recommended to use 32-bit equivalent

2021/09/17 04:47 · prokushev · [0 Comments](#)

2021/08/20 03:18 · prokushev · [0 Comments](#)

## DosClose

This call closes a handle to a file, pipe, or device.

### Syntax

```
DosClose (FileHandle)
```

### Parameters

- FileHandle ([HFILE](#)) - input : Handle returned by a previous [DosOpen](#), [DosMakeNmPipe](#), or [DosMakePipe](#) call.

### Return Code

```
rc ([[USHORT]]) - return
```

Return code descriptions are:

- 0 NO\_ERROR
- 2 ERROR\_FILE\_NOT\_FOUND
- 5 ERROR\_ACCESS\_DENIED
- 6 ERROR\_INVALID\_HANDLE

### Remarks

Issuing DosClose with the handle to a file closes a handle to a file, pipe, or device.

If one or more additional handles to a file have been created with [DosDupHandle](#), the directory is not updated and all internal buffers are not written to the medium until DosClose has been issued for the duplicated handles.

Closing a handle to a device causes the device to be notified of the close, if appropriate.

## Named Pipe Considerations

DosClose closes a named pipe by handle. When all handles referencing one end of a pipe are closed, the pipe is considered broken.

If the client end closes, no other process can re-open the pipe until the serving end issues a [DosDisconnectNmPipe](#) followed by a [DosConnectNmPipe](#).

If the server end closes when the pipe is already broken, it is deallocated immediately; otherwise, the pipe is not deallocated until the last client handle is closed.

## Example Code

### C Binding

```
#define INCL_DOSFILEMGR

USHORT rc = DosClose(FileHandle);

HFILE FileHandle; /* File handle */
USHORT rc; /* return code */
```

This example opens a file, then closes it.

```
#define INCL_DOSFILEMGR

#define OPEN_FILE 0x01
#define CREATE_FILE 0x10
#define FILE_ARCHIVE 0x20
#define FILE_EXISTS OPEN_FILE
#define FILE_NOEXIST CREATE_FILE
#define DASD_FLAG 0
#define INHERIT 0x80
#define WRITE_THRU 0
#define FAIL_FLAG 0
#define SHARE_FLAG 0x10
#define ACCESS_FLAG 0x02

#define FILE_NAME "test.dat"
#define FILE_SIZE 800L
#define FILE_ATTRIBUTE FILE_ARCHIVE
#define RESERVED 0L

HFILE FileHandle;
USHORT Wrote;
USHORT Action;
PSZ FileData[100];
USHORT rc;
```

```

Action = 2;
strcpy(FileData, "Data...");

if(!DosOpen(FILE_NAME,
            &FileHandle,           /* File path name */
            &Action,              /* File handle */
            FILE_SIZE,             /* Action taken */
            FILE_ATTRIBUTE,        /* File primary allocation */
            FILE_EXISTS | FILE_NOEXISTS, /* File attribute */
            DASD_FLAG | INHERIT |      /* Open function type */
            WRITE_THRU | FAIL_FLAG |    /* Open mode of the file */
            SHARE_FLAG | ACCESS_FLAG,
            RESERVED))           /* Reserved (must be zero) */
rc = DosClose(FileHandle); /* File Handle */

```

## MASM Binding

```

EXTRN DosClose:FAR
INCL_DOSFILEMGR EQU 1

PUSH WORD FileHandle ;File handle
CALL DosClose

```

Returns WORD

## Note

Text based on [http://www.edm2.com/index.php/DosClose\\_\(FAPI\)](http://www.edm2.com/index.php/DosClose_(FAPI))

Family API	
DOS	Process Manager DosBeep DosExit DosSleep DosExecPgm
	File Manager DosChDir DosChgFilePtr DosClose DosDelete DosDupHandle DosMkDir DosMove DosQCurDir DosQCurDisk DosSet FileMode DosOpen DosQFileInfo DosRead DosQ FileMode DosQFSInfo DosQVerify DosRmDir DosSelectDisk DosFindClose DosFindFirst DosFindNext DosSet FileInfo DosSet Verify DosWrite DosFileLocks DosSet FHandState DosNewSize DosBufReset DosQFHandState DosSet FInfo
	Memory Manager DosFreeSeg DosSubAlloc DosSubFree DosSubSet DosAlloc Huge DosAlloc Seg DosRealloc Huge DosRealloc Seg DosGet Huge Shift DosCreate CS Alias
	NLS DosCaseMap DosGet Ctry Info DosGet DBCSEv DosSet Ctry Code DosGet Collate DosGet Message DosIns Message DosPut Message
	Date and Time DosSet Date Time DosGet Date Time
	Devices DosDevConfig DosDevIOCtl DosDevIOCtl2
	Signals DosHold Signal DosSet Sig Handler
	Misc BadDynLink DosGet Env DosGet Machine Mode DosGet Version DosError DosErr Class DosSet Vec
KBD KbdCharIn KbdFlush Buffer KbdGet Status KbdSet Status KbdStringIn KbdPeek	

Family API	
VIO	<a href="#">VioGetBuf</a> <a href="#">VioGetConfig</a> <a href="#">VioGetCurPos</a> <a href="#">VioGetCurType</a> <a href="#">VioGetPhysBuf</a> <a href="#">VioReadCellStr</a> <a href="#">VioReadCharStr</a> <a href="#">VioScrollUp</a> <a href="#">VioScrollDn</a> <a href="#">VioScrollLf</a> <a href="#">VioScrollRt</a> <a href="#">VioScrUnLock</a> <a href="#">VioSetCurPos</a> <a href="#">VioSetCurType</a> <a href="#">VioSetMode</a> <a href="#">VioGetMode</a> <a href="#">VioShowBuf</a> <a href="#">VioWrtCellStr</a> <a href="#">VioWrtCharStr</a> <a href="#">VioWrtCharStrAtt</a> <a href="#">VioWrtNAttr</a> <a href="#">VioWrtNCell</a> <a href="#">VioWrtNChar</a> <a href="#">VioWrtTTY</a> <a href="#">VioScrLock</a> <a href="#">VioPopUp</a>
Tools	BIND
Modules	<a href="#">DOSCALLS.DLL</a> <a href="#">VIOCALLS.DLL</a> <a href="#">KBDCALLS.DLL</a> <a href="#">MSG.DLL</a>
Libraries	<a href="#">API.LIB</a> <a href="#">OS2386.LIB</a> <a href="#">FAPI.LIB</a> <a href="#">DOSCALLS.LIB</a> <a href="#">SUBCALLS.LIB</a>

2018/08/25 15:05 · prokushev · [0 Comments](#)

From:

<https://ftp.osfree.org/doku/> - osFree wiki

Permanent link:

<https://ftp.osfree.org/doku/doku.php?id=en:docs:fapi:dosclose&rev=1631853297>Last update: **2021/09/17 04:34**