



This is part of **Family API** which allow to create dual-os version of program runs under OS/2 and DOS

Note: This is legacy API call. It is recommended to use 32-bit equivalent

2021/09/17 04:47 · prokushhev · [0 Comments](#)

2021/08/20 03:18 · prokushhev · [0 Comments](#)

DosSetFileInfo

This call sets attribute and extended attribute information for a file.

Syntax

```
DosSetFileInfo (FileHandle, FileInfoLevel, FileInfoBuf, FileInfoBufSize)
```

Parameters

- FileHandle ([HFILE](#)) - input : File handle.
- FileInfoLevel ([USHORT](#)) - input : Level of file information being set. A value of 1 or 2 can be specified. The structures described in FileInfoBuf indicate the information being set for each of these levels.
- FileInfoBuf ([PBYTE](#)) - input : Address of the storage area containing the structures for file information levels.
- FileInfoBufSize ([USHORT](#)) - input : Length of FileInfoBuf.

Level 1 Information

FileInfoBuf contains the following structure, to which information is specified in the following format:

filedate ([FDATE](#)) : Structure containing the date of file creation.

| Bit | Description |
|------|------------------------------------|
| 15-9 | Year, in binary, of file creation |
| 8-5 | Month, in binary, of file creation |
| 4-0 | Day, in binary, of file creation |

filetime ([FTIME](#)) : Structure containing the time of file creation.

| Bit | Description |
|-------|--|
| 15-11 | Hours, in binary, of file creation |
| 10-5 | Minutes, in binary, of file creation |
| 4-0 | Seconds, in binary number of two-second increments, of file creation |

fileaccessdate ([FDATE](#)) : Structure containing the date of last access. See [FDATE](#) in filedate.

fileaccesstime ([FTIME](#)) : Structure containing the time of last access. See [FTIME](#) in filetime.

writeaccessdate ([FDATE](#)) : Structure containing the date of last write. See [FDATE](#) in filedate.

writeaccesstime ([FTIME](#)) : Structure containing the time of last write. See [FTIME](#) in filetime.

filesize ([ULONG](#)) : File size.

filealloc ([ULONG](#)) : Allocated file size.

fileattrib ([USHORT](#)) : Attributes of the file, defined in DosSet FileMode.

Level 2 Information

FileInfoBuf contains an [EAOP](#) structure, which has the following format:

fpGEAList ([PGEALIST](#)) : Address of GEAList. GEAList is a packed array of variable length "get EA" structures, each containing an EA name and the length of the name.

fpFEAList ([PFEALIST](#)) : Address of FEAList. FEAList is a packed array of variable length "full EA" structures, each containing an EA name and its corresponding value, as well as the lengths of the name and the value.

oError ([ULONG](#)) : Offset into structure where error has occurred.

Level 2 sets a series of EA name/value pairs. On input, FileInfoBuf is an EAOP structure above.

fpGEAList is ignored. fpFEAList points to a data area where the relevant FEA list is to be found. oError is ignored. Following is the format of the FEAList structure:

cbList ([ULONG](#)) : Length of the FEA list, including the length itself.

list ([FEA](#)) : List of FEA structures. An FEA structure has the following format:

Flags ([BYTE](#)) : Bit indicator describing the characteristics of the EA being defined.

| Bit | Description |
|-----|----------------------------------|
| 7 | Critical EA |
| 6-0 | Reserved and must be set to zero |

If bit 7 is set to 1, this indicates a critical EA. If bit 7 is 0, this means the EA is noncritical; that is, the EA is not essential to the intended use by an application of the file with which it is associated.

cbName ([BYTE](#)) : Length of EA ASCIIZ name, which does not include the null character.

cbValue ([USHORT](#)) : Length of EA value, which cannot exceed 64KB.

szName ([PSZ](#)) : Address of the ASCIIZ name of EA.

aValue ([PSZ](#)) : Address of the free-format value of EA.

'Note:' The szName and aValue fields are not included as part of header or include files. Because of their variable lengths, these entries must be built manually.

On output, fpGEAList is unchanged. fpFEAList is unchanged as is the area pointed to by fpFEAList. If an error occurred during the set, oError is the offset of the FEA where the error occurred. The API return code is the error code corresponding to the condition generating the error. If no error occurred, oError is undefined.

Return Code

- 0 NO_ERROR
- 1 ERROR_INVALID_FUNCTION
- 5 ERROR_ACCESS_DENIED
- 6 ERROR_INVALID_HANDLE
- 87 ERROR_INVALID_PARAMETER
- 122 ERROR_INSUFFICIENT_BUFFER
- 124 ERROR_INVALID_LEVEL
- 130 ERROR_DIRECT_ACCESS_HANDLE
- 254 ERROR_INVALID_EA_NAME
- 255 ERROR_EA_LIST_INCONSISTENT

Remarks

DosSetFileInfo is successful only when the file is opened for write access, with a deny-both sharing mode specified for access to the file by other processes. If the file is already opened with conflicting sharing rights, the call to [DosOpen](#) or [DosOpen2](#) will fail.

A 0 value in the date and time components of a field does not change the field. For example, if both "last write date" and "last write time" are specified as 0 in the Level 1 information structure, then both attributes of the file are left unchanged. If either "last write date" or "last write time" are specified as non-zero, both attributes of the file are set to the new values.

The FAT file system supports modification of only the dates and times of the last write. Creation and last access dates and times are not affected.

The last modification date and time will get changed if the extended attributes are modified.

Family API Considerations

It is not possible to create a label with leading blank characters in DOS mode, because of restrictions on the previous Interrupt 21h function call (create an FCB type file), which must be used by FAPI.

Example Code

C Binding

```

typedef struct _FDATE { /* fdate */
    unsigned day : 5;      /* binary day for directory entry */
    unsigned month : 4;    /* binary month for directory entry */
    unsigned year : 7;     /* binary year for directory entry */
} FDATE;

typedef struct _FTIME { /* ftime */
    unsigned twosecs : 5;  /* binary number of two-second increments */
    unsigned minutes : 6;  /* binary number of minutes */
    unsigned hours : 5;   /* binary number of hours */
} FTIME;

typedef struct _FILESTATUS { /* fsts */
    FDATE fdateCreation;  /* date of file creation */
    FTIME ftimeCreation;  /* time of file creation */
    FDATE fdateLastAccess; /* date of last access */
    FTIME ftimeLastAccess; /* time of last access */
    FDATE fdateLastWrite; /* date of last write */
    FTIME ftimeLastWrite; /* time of last write */
    ULONG cbFile;          /* file size (end of data) */
    ULONG cbFileAlloc;     /* file allocated size */
    USHORT attrFile;       /* attributes of the file */
} FILESTATUS;

typedef struct _GEA { /* gea */
    BYTE cbName;           /* name length not including NULL */
    CHAR szName[1];        /* attribute name */
} GEA;

typedef struct _GEALIST { /* geal */
    ULONG cbList;          /* total bytes of structure including full list */
    GEA list[1];           /* variable length GEA structures */
} GEALIST;

typedef struct _FEA { /* fea */
    BYTE fEA;              /* flags */
    BYTE cbName;            /* name length not including NULL */
}

```

```

USHORT cbValue;           /* value length */

} FEA;

typedef struct _FEALIST { /* feal */

ULONG cbList;             /* total bytes of structure including full list */
FEA list[1];              /* variable length FEA structures */

} FEALIST;

typedef struct _EAOP {     /* eaop */

PGEALIST fpGEAList;       /* general EA list */
PFEALIST fpFEAList;       /* full EA list */
ULONG oError;

} EAOP;

#define INCL_DOSFILEMGR

USHORT rc = DosSetFileInfo(FileHandle, FileInfoLevel, FileInfoBuf,
                           FileInfoBufSize);

HFILE          FileHandle;      /* File handle */
USHORT         FileInfoLevel;   /* File info data required */
PBYTE          FileInfoBuf;    /* File info buffer */
USHORT         FileInfoBufSize; /* File info buffer size */

USHORT         rc;             /* return code */

```

MASM Binding

```

FDATE  struc
    fdate_fs dw ?
FDATE  ends

FTIME  struc
    ftime_fs dw ?
FTIME  ends

FILESTATUS struc
    fsts_fdateCreation dw (size FDATE)/2 dup (?) ;date of file creation
    fsts_ftimeCreation dw (size FTIME)/2 dup (?) ;time of file creation
    fsts_fdateLastAccess dw (size FDATE)/2 dup (?) ;date of last access

```

```

fsts_ftimeLastAccess dw (size FTIME)/2 dup (?) ;time of last access
fsts_fdateLastWrite dw (size FDATETIME)/2 dup (?) ;date of last write
fsts_ftimeLastWrite dw (size FTIME)/2 dup (?) ;time of last write
fsts_cbFile dd ? ;file size (end of data)
fsts_cbFileAlloc dd ? ;file allocated size
fsts_attrFile dw ? ;attributes of the file

FILESTATUS ends

GEA      struc

    gea_cbName      db ?          ;name length not including NULL
    gea_szName      db 1 dup (?) ;attribute name

GEA      ends

GEALIST   struc

    geal_cbList     dd ?          ;total bytes of structure including full list
    geal_list       db size GEA * 1 dup (?) ;variable length GEA structures

GEALIST   ends

FEA      struc

    fea_fEA         db ? ;flags
    fea_cbName      db ? ;name length not including NULL
    fea_cbValue     dw ? ;value length

FEA      ends

FEALIST   struc

    feal_cbList     dd ?          ;total bytes of structure including full list
    feal_list       db size FEA * 1 dup (?) ;variable length FEA structures

FEALIST   ends

EAOP      struc

    eaop_fpGEAList dd ? ;general EA list
    eaop_fpFEAList dd ? ;full EA list
    eaop_oError     dd ? ;

EAOP      ends

EXTRN  DosSetFileInfo:FAR
INCL_DOSFILEMGR EQU 1

PUSH    WORD     FileHandle      ;File handle
PUSH    WORD     FileInfoLevel   ;File info data required

```

```
PUSH@ OTHER FileInfoBuf ;File info buffer
PUSH WORD FileInfoBufSize ;File info buffer size
CALL DosSetFileInfo
```

Returns WORD

Note

Text based on [http://www.edm2.com/index.php/DosSetFileInfo_\(FAPI\)](http://www.edm2.com/index.php/DosSetFileInfo_(FAPI))

| Family API | | |
|------------|-----------------|--|
| DOS | Process Manager | DosBeep DosExit DosSleep DosExecPgm |
| | File Manager | DosChDir DosChgFilePtr DosClose DosDelete DosDupHandle DosMkDir DosMove DosQCurDir DosQCurDisk DosSet FileMode DosOpen DosQFileInfo DosRead DosQ FileMode DosQFSInfo DosQVerify DosRmDir DosSelectDisk DosFindClose DosFindFirst DosFindNext DosSetFileInfo DosSetVerify DosWrite DosFileLocks DosSetFHandState DosNewSize DosBufReset DosQFHandState DosSetFSinfo |
| | Memory Manager | DosFreeSeg DosSubAlloc DosSubFree DosSubSet DosAllocHuge DosAllocSeg DosReallocHuge DosReallocSeg DosGetHugeShift DosCreateCSAlias |
| | NLS | DosCaseMap DosGetCtryInfo DosGetDBCSEv DosSetCtryCode DosGetCollate DosGetMessage DosInsMessage DosPutMessage |
| | Date and Time | DosSetDateTime DosGetDateTime |
| | Devices | DosDevConfig DosDevIOCtl DosDevIOCtl2 |
| | Signals | DosHoldSignal DosSetSigHandler |
| | Misc | BadDynLink DosGetEnv DosGetMachineMode DosGetVersion DosError DosErrClass DosSetVec |
| KBD | | KbdCharIn KbdFlushBuffer KbdGetStatus KbdSetStatus KbdStringIn KbdPeek |
| VIO | | VioGetBuf VioGetConfig VioGetCurPos VioGetCurType VioGetPhysBuf VioReadCellStr VioReadCharStr VioScrollUp VioScrollDn VioScrollLf VioScrollRt VioScrUnLock VioSetCurPos VioSetCurType VioSetMode VioGetMode VioShowBuf VioWrtCellStr VioWrtCharStr VioWrtCharStrAtt VioWrtNAttr VioWrtNCell VioWrtNChar VioWrtTTY VioScrLock VioPopUp |
| Tools | | BIND |
| Modules | | DOSCALLS.DLL VIOCALS.DLL KBDCALLS.DLL MSG.DLL |
| Libraries | | API.LIB OS2386.LIB FAPI.LIB DOSCALLS.LIB SUBCALLS.LIB |

2018/08/25 15:05 · prokushev · 0 Comments

From:
<https://ftp.osfree.org/doku/> - osFree wiki

Permanent link:
<https://ftp.osfree.org/doku/doku.php?id=en:docs:fapi:dossetfileinfo>

Last update: 2021/09/17 08:32

