

This call frees the logical-to-physical keyboard bond created by [KbdGetFocus](#).

Syntax

KbdFreeFocus (KbdHandle)

Parameters

;KbdHandle (HKBD) - input: Default keyboard or the logical keyboard.

Return Code

;rc (USHORT) - return:Return code descriptions are: ::0 NO_ERROR ::439
ERROR_KBD_INVALID_HANDLE ::445 ERROR_KBD_FOCUS_REQUIRED ::464 ERROR_KBD_DETACHED
::504 ERROR_KBD_EXTENDED_SG

Remarks

KbdFreeFocus may be replaced by issuing [KbdRegister](#). Unlike other keyboard subsystem functions, the replaced KbdFreeFocus is called only if there is an outstanding focus.

Bindings

C

```
<PRE> #define INCL_KBD  
  
USHORT rc = KbdFreeFocus(KbdHandle); HKBD KbdHandle; /* Keyboard handle */  
  
USHORT rc; /* return code */ </PRE>
```

MASM

```
<PRE> EXTRN KbdFreeFocus:FAR INCL_KBD EQU 1  
  
PUSH WORD KbdHandle ;Keyboard handle CALL KbdFreeFocus  
  
Returns WORD </PRE>
```

[Kbd](#)

From:

<https://ftp.osfree.org/doku/> - **osFree wiki**

Permanent link:

<https://ftp.osfree.org/doku/doku.php?id=en:docs:fapi:kbdreefocus&rev=1633521593>

Last update: **2021/10/06 11:59**

