 This is part of **Family API** which allow to create dual-os version of program runs under OS/2 and DOS

Note: This is legacy API call. It is recommended to use 32-bit equivalent

2021/09/17 04:47 · prokushev · 0 Comments
2021/08/20 03:18 · prokushev · 0 Comments

KbdFreeFocus

This call frees the logical-to-physical keyboard bond created by KbdGetFocus.

Syntax

```
KbdFreeFocus (KbdHandle)
```

Parameters

- KbdHandle (HKBD) - input: Default keyboard or the logical keyboard.

Return Code

rc (USHORT) - return:Return code descriptions are:

- 0 NO_ERROR
- 439 ERROR_KBD_INVALID_HANDLE
- 445 ERROR_KBD_FOCUS_REQUIRED
- 464 ERROR_KBD_DETACHED
- 504 ERROR_KBD_EXTENDED_SG

Remarks

KbdFreeFocus may be replaced by issuing KbdRegister. Unlike other keyboard subsystem functions, the replaced KbdFreeFocus is called only if there is an outstanding focus.

Bindings

C

```
#define INCL_KBD

USHORT  rc = KbdFreeFocus(KbdHandle);
HKBD    KbdHandle;      /* Keyboard handle */

USHORT  rc;             /* return code */
```

MASM

```
EXTRN  KbdFreeFocus:FAR
INCL_KBD            EQU 1

PUSH   WORD    KbdHandle      ;Keyboard handle
CALL   KbdFreeFocus

Returns WORD
```

From:
https://ftp.osfree.org/doku/ - **osFree wiki**

Permanent link:
https://ftp.osfree.org/doku/doku.php?id=en:docs:fapi:kbdfreefocus&rev=1634998922

Last update: **2021/10/23 14:22**