



This is part of **Family API** which allow to create dual-os version of program runs under OS/2 and DOS

Note: This is legacy API call. It is recommended to use 32-bit equivalent

2021/09/17 04:47 · prokushev · [0 Comments](#)

2021/08/20 03:18 · prokushev · [0 Comments](#)

KbdPeek

This call returns any available character data record from the keyboard without removing it from the buffer.

Syntax

```
KbdPeek (CharData, KbdHandle)
```

```
</cdoe>
```

```
===== Parameters =====
```

```
* CharData ([[PKBDKEYINFO]]) - output : Address of the character data information:
```

```
* asciicharcode ([[UCHAR]]) : ASCII character code. The scan code received from the keyboard is translated to the ASCII character code.
```

```
* scancode ([[UCHAR]]) : Code received from the keyboard hardware.
```

```
* status ([[UCHAR]]) : State of the keystroke event:
```

```
^ Bit ^ Description ^
```

```
| 7-6 | 00 = Undefined. |
```

```
| ::: | 01 = Final character, interim character flag off. |
```

```
| ::: | 10 = Interim character. |
```

```
| ::: | 11 = Final character, interim character flag on. |
```

```
| 5 | 1 = Immediate conversion requested. |
```

```
| 4-2 | Reserved, set to zero. |
```

```
| 1 | 0 = Scan code is a character. |
```

```
| ::: | 1 = Scan code is not a character; it is an extended key code from the keyboard. |
```

```
| 0 | 1 = Shift status returned without character. |
```

```
* reserved ([[UCHAR]]) : NLS shift status. Reserved, set to zero.
```

```
* shiftkeystat ([[USHORT]]) : Shift key status.
```

```
^ Bit ^ Description ^
```

```
| 15 | SysReq key down |
```

```
| 14 | CapsLock key down |
```

```
| 13 | NumLock key down |
```

```
| 12 | ScrollLock key down |
| 11 | Right Alt key down |
| 10 | Right Ctrl key down |
| 9 | Left Alt key down |
| 8 | Left Ctrl key down |
| 7 | Insert on |
| 6 | CapsLock on |
| 5 | NumLock on |
| 4 | ScrollLock on |
| 3 | Either Alt key down |
| 2 | Either Ctrl key down |
| 1 | Left Shift key down |
| 0 | Right Shift key down |
```

* `time` (`[[ULONG]]`) : Time stamp indicating when a key was pressed. It is specified in milliseconds from the `time` the `system` was started.

* `KbdHandle` (`[[HKBD]]`) - `input` : Default keyboard or the logical keyboard.

==== Return Code ====

`rc` (`[[USHORT]]T`) - `return`

Return code descriptions are:

```
* 0      NO_ERROR
* 439    ERROR_KBD_INVALID_HANDLE
* 445    ERROR_KBD_FOCUS_REQUIRED
* 447    ERROR_KBD_KEYBOARD_BUSY
* 464    ERROR_KBD_DETACHED
* 504    ERROR_KBD_EXTENDED_SG
```

==== Remarks ====

On an enhanced keyboard, the secondary enter key returns the normal character 0DH and a scan code of E0H.

Double-byte character codes (DBCS) require two **function** calls to obtain the entire code.

If shift report is set with `KbdSetStatus` the `CharData` record returned, reflects changed shift information only.

Extended ASCII codes are identified with the status byte, bit 1 on and the ASCII character code being either 00H or E0H. **Both** conditions must be satisfied **for** the character to be an extended keystroke. **For** extended ASCII codes, the scan code byte returned is the second code (extended code). **Usually** the extended ASCII code is the scan code of the primary key that was pressed.

A thread in the foreground session that repeatedly polls the keyboard with `KbdCharIn` (with no wait), can prevent all regular priority class threads

from executing. If polling must be used and a minimal amount of other processing is being performed, the thread should periodically yield the CPU by issuing a DosSleep call for an interval of at least 5 milliseconds.

==== Family API Considerations ====

Some options operate differently in the DOS mode than in the OS/2 mode. Therefore, the following restrictions apply to KbdPeek when coding for the DOS mode:

- * The CharData structure includes everything except the time stamp.
- * Interim character is not supported.
- * Status can be 0 or 1.
- * KbdHandle is ignored.

==== Bindings =====

====C Binding=====

<code c>

```
typedef struct _KBDKEYINFO { /* kbc_i */
    UCHAR    chChar;        /* ASCII character code */
    UCHAR    chScan;       /* Scan Code */
    UCHAR    fbStatus;     /* State of the character */
    UCHAR    bNlsShift;    /* Reserved (set to zero) */
    USHORT   fsState;      /* State of the shift keys */
    ULONG    time;         /* Time stamp of keystroke (ms since ipl) */
}KBDKEYINFO;
```

```
#define INCL_KBD
```

```
USHORT rc = KbdPeek(CharData, KbdHandle);
```

```
PKBDKEYINFO CharData; /* Buffer for data */
```

```
HKBD KbdHandle; /* Keyboard handle */
```

```
USHORT rc; /* return code */
```

MASM Binding

```
KBDKEYINFO struc
    kbc_i_chChar db ? ;ASCII character code
    kbc_i_chScan db ? ;Scan Code
    kbc_i_fbStatus db ? ;State of the character
    kbc_i_bNlsShift db ? ;Reserved (set to zero)
    kbc_i_fsState dw ? ;state of the shift keys
    kbc_i_time dd ? ;time stamp of keystroke (ms since ipl)
KBDKEYINFO ends
```

```
EXTRN KbdPeek:FAR
```

```
INCL_KBD EQU 1
```

PUSH@ OTHER CharData ;Buffer for data
PUSH **WORD** KbdHandle ;Keyboard handle
CALL KbdPeek

Returns **WORD**

Note

Text based on [http://www.edm2.com/index.php/KbdPeek_\(FAPI\)](http://www.edm2.com/index.php/KbdPeek_(FAPI))

Family API		
DOS	Process Manager	DosBeep DosExit DosSleep DosExecPgm
	File Manager	DosChDir DosChgFilePtr DosClose DosDelete DosDupHandle DosMkDir DosMove DosQCurDir DosQCurDisk DosSetFileMode DosOpen DosQFileInfo DosRead DosQFileMode DosQFSInfo DosQVerify DosRmdir DosSelectDisk DosFindClose DosFindFirst DosFindNext DosSetFileInfo DosSetVerify DosWrite DosFileLocks DosSetFHandState DosNewSize DosBufReset DosQFHandState DosSetFSInfo DosShutdown
	Memory Manager	DosFreeSeg DosSubAlloc DosSubFree DosSubSet DosAllocHuge DosAllocSeg DosReallocHuge DosReallocSeg DosGetHugeShift DosCreateCSAlias
	NLS	DosCaseMap DosGetCtryInfo DosGetDBCSEv DosSetCtryCode DosGetCollate DosGetMessage DosInsMessage DosPutMessage
	Date and Time	DosSetDateTime DosGetDateTime
	Devices	DosDevConfig DosDevIOct1 DosDevIOct2
	Signals	DosHoldSignal DosSetSigHandler
	Misc	BadDynLink DosGetEnv DosGetMachineMode DosGetVersion DosError DosErrClass DosSetVec
KBD	KbdCharIn KbdFlushBuffer KbdGetStatus KbdSetStatus KbdStringIn KbdPeek	
VIO	VioGetBuf VioGetConfig VioGetCurPos VioGetCurType VioGetPhysBuf VioReadCellStr VioReadCharStr VioScrollUp VioScrollDn VioScrollLf VioScrollRt VioScrUnLock VioSetCurPos VioSetCurType VioSetMode VioGetMode VioShowBuf VioWrtCellStr VioWrtCharStr VioWrtCharStrAtt VioWrtNAttr VioWrtNCell VioWrtNChar VioWrtTTY VioScrLock VioPopUp	
Tools	BIND	
Modules	DOSCALLS.DLL VIOCALLS.DLL KBDCALLS.DLL MSG.DLL	
Libraries	API.LIB OS2386.LIB FAPI.LIB DOSCALLS.LIB SUBCALLS.LIB	

2018/08/25 15:05 · prokushev · 0 Comments

From: <https://ftp.osfree.org/doku/> - **osFree wiki**

Permanent link: <https://ftp.osfree.org/doku/doku.php?id=en:docs:fapi:kbdpeek&rev=1632015462>

Last update: **2021/09/19 01:37**

