This call returns the number of buttons supported on the installed mouse driver.

Syntax

MouGetNumButtons (NumberOfButtons, DeviceHandle)

Parameters

;NumberOfButtons (PUSHORT) - output : Address of the number of physical buttons. The return values for the number of buttons supported are: ::1 - One mouse button ::2 - Two mouse buttons ::3 - Three mouse buttons. ; DeviceHandle (HMOU) - input : Handle of the mouse device from a previous MouOpen.

Return Code

;rc (USHORT) - return:Return code descriptions are: *385 ERROR_MOUSE_NO_DEVICE *466 ERROR_MOU_DETACHED *501 ERROR_MOUSE_NO_CONSOLE *505 ERROR_MOU_EXTENDED_SG

Bindings

C

<PRE> #define INCL_MOU

USHORT rc = MouGetNumButtons(NumberOfButtons, DeviceHandle);

PUSHORT NumberOfButtons; /* Number of mouse buttons */ HMOU DeviceHandle; /* Mouse device handle */

USHORT rc; /* return code */ </PRE>

MASM

<PRE> EXTRN MouGetNumButtons:FAR INCL_MOU EQU 1

PUSH@ WORD NumberOfButtons ;Number of mouse buttons PUSH WORD DeviceHandle ;Mouse device handle CALL MouGetNumButtons

Returns WORD </PRE>

Example

```
HMOU DeviceHandle;
...
```

```
MouOpen(0L, &DeviceHandle);
MouGetNumButtons(&NumberOfButtons, DeviceHandle);
```

Mou

From:
https://ftp.osfree.org/doku/ - **osFree wiki**

Permanent link:
https://ftp.osfree.org/doku/doku.php?id=en:docs:fapi:mougetnummickeys&rev=1633526420

Last update: **2021/10/06 13:20**