

This call performs one of the following functions; set palette registers, sets the overscan (border) colour, set the blink/background intensity switch, set color registers, set the underline location, or set the target VioSetMode display configuration.

Syntax

VioSetState (RequestBlock, VioHandle)

Parameters

;RequestBlock (PVOID) - input : Address of the video state structures consisting of six different structures depending on the request type: ::0 - Set palette registers ::1 - Set overscan (border) color ::2 - Set blink/background intensity switch ::3 - Set color registers ::4 - Reserved ::5 - Set underline location ::6 - Set target VioSetMode display configuration ::7 - Reserved The six structures, depending on request type, are: {`! ||Applies to||length (USHORT) - input : Length of structure, including length.||reqtype (USHORT) - input||`

VIOPALSTATE	EGA, VGA, or IBM Personal System/2 Display Adapter	38 - Maximum valid value.	Request type 0 for palette registers.
-------------	--	---------------------------	---------------------------------------

:palette (USHORT) - input: First palette register in the palette register sequence; must be specified in the range 0 through 15. The palette registers are returned in sequential order. The number returned is based upon length. :color (USHORT*(length-6)/2) - input : Color value for each palette register. The maximum number of entries in the color value array is 16.

VIOOVERSCAN	CGA, VGA, or IBM Personal System/2 Display Adapter	Only valid value.	Request type 1 for overscan (border) color.
VIOINTENSITY	CGA, EGA, MCGA, VGA, or IBM Personal System/2 Display Adapter	Only valid value.	Request type 2 for blink/background intensity switch.

:switch (USHORT) - input : Switch set as: ::0 - Blinking foreground colors enabled. ::1 - High intensity background colors enabled.

VIOCOLORREG	VGA, or IBM Personal System/2 Display Adapter	12 - Only valid value.	Request type 3 for color registers.
-------------	---	------------------------	-------------------------------------

:first color (USHORT) - input : First color register to set in the color register sequence; must be specified in the range 0 through 255. The color registers are set in sequential order. :number color (USHORT) - input : Number of color registers to set; must be specified in the range 1 through 256. :dataarea (PCH) - input : Far address of a data area containing one three-byte entry for each color register to be set. The format of each entry is as follows: ::Byte 1 - Red value ::Byte 2 - Green value ::Byte 3 - Blue value

			4
VIOSETULINELOC	EGA, VGA, or IBM Personal System/2 Display Adapter	Only valid value.	Request type 5 to set the scan line for underlining. Underlining is enabled only when the foreground color is 1 or 9.


```
typedef VIOINTENSITY far *PVIOINTENSITY;
```

```
typedef struct _VIOCOLORREG { /* viocreg */
```

```
    USHORT  cb;
    USHORT  type;
    USHORT  firstcolorreg;
    USHORT  numcolorregs;
    PCH     colorregaddr;
}VIOCOLORREG;
```

```
typedef VIOCOLORREG far *PVIOCOLORREG;
```

```
typedef struct _VIOSETULINELOC { /* viouline */
```

```
    USHORT  cb;
    USHORT  type;
    USHORT  scanline;
}VIOSETULINELOC;
```

```
typedef VIOSETULINELOC far *PVIOSETULINELOC;
```

```
typedef struct _VIOSETTARGET { /* viosett */
```

```
    USHORT  cb;
    USHORT  type;
    USHORT  defaultalgorithm;
}VIOSETTARGET;
```

```
typedef VIOSETTARGET far *PVIOSETTARGET;
```

```
#define INCL_VIO
```

```
USHORT rc = VioSetState(RequestBlock, VioHandle);
```

```
PVOID RequestBlock; /* Request block */ HVIO VioHandle; /* Video handle */
```

```
USHORT rc; /* return code */ </PRE>
```

MASM

```
<PRE> VIOPALSTATE struc
```

```
    viopal_cb          dw ? ;Length of this structure in bytes
    viopal_type        dw ? ;Request type=0 get palette registers
    viopal_iFirst      dw ? ;First palette register to return
    viopal_acolor      dw 1 dup (?) ;Color value palette register
```

```
VIOPALSTATE ends
```

VIOOVERSCAN struc

```
vioos_cb          dw ? ;Length of this structure
vioos_type        dw ? ;Request type=1 get overscan (border) color
vioos_color       dw ? ;Color value
```

VIOOVERSCAN ends

VIOINTENSITY struc

```
vioint_cb        dw ? ;Length of this structure
vioint_type      dw ? ;Request type=2 get blink/background
                 ; intensity switch
vioint_fs        dw ? ;Value of blink/background switch
```

VIOINTENSITY ends

VIOCOLORREG struc

```
viocreg_cb       dw ? ;
viocreg_type     dw ? ;
viocreg_firstcolorreg dw ? ;
viocreg_numcolorregs dw ? ;
viocreg_colorregaddr dd ? ;
```

VIOCOLORREG ends

VIOSETULINELOC struc

```
viouline_cb      dw ? ;
viouline_type    dw ? ;
viouline_scanline dw ? ;
```

VIOSETULINELOC ends

VIOSETTARGET struc

```
viosett_cb       dw ? ;
viosett_type     dw ? ;
viosett_defaultalgorithm dw ? ;
```

VIOSETTARGET ends

EXTRN VioSetState:FAR INCL_VIO EQU 1

PUSH@ OTHER RequestBlock ;Request block PUSH WORD VioHandle ;Video handle CALL VioSetState

Returns WORD </PRE>

[http://www.edm2.com/index.php/VioSetState_\(OS/2_1.x\)](http://www.edm2.com/index.php/VioSetState_(OS/2_1.x))

From:
<https://ftp.osfree.org/doku/> - **osFree wiki**

Permanent link:
<https://ftp.osfree.org/doku/doku.php?id=en:docs:fapi:vioresetstate&rev=1630822828>

Last update: **2021/09/05 06:20**

