

# New Executable file format

New Executable (NE) file format used by set of operating system including OS/2, Windows, Multitasking MS-DOS 4 and set of DOS Extenders. It is designed to be store on disk and in-memory usage. In-disk format is same for all OSes, but In-memory usage is mostly specific for Windows systems.

<b>Offset</b>	<b>Size</b>	<b>Name</b>	<b>Description</b>
00h	WORD	ne_magic	Signature word NEMAGIC
<b>On-disk</b>			
02h	BYTE	ne_ver	Version number of the linker
03h	BYTE	ne_rev	Revision number of the linker
<b>In-memory</b>			
02h	WORD	count	Usage count (ne_ver/ne_rev on disk)
04h	WORD	ne_enttab	Entry Table file offset, relative to the beginning of the segmented EXE header
<b>On-disk</b>			
06h	WORD	ne_cbenttab	Number of bytes in the entry table
<b>In-memory</b>			
06h	WORD	next	Selector to next module
<b>On-disk</b>			
08h	DWORD	ne_crc	32-bit CRC of entire contents of file. These words are taken as 00 during the calculation
<b>In-memory</b>			
08h	WORD	dgroup_entry	Near ptr to segment entry for DGROUP
0Ah	WORD	fileinfo	Near ptr to file info (OFSTRUCT)
0Ch	WORD	ne_flags	Flag word
0Eh	WORD	ne_autodata	Segment number of automatic data segment. This value is set to zero if SINGLEDATA and MULTIPLEDATA flag bits are clear, NOAUTODATA is indicated in the flags word. A Segment number is an index into the module's segment table. The first entry in the segment table is segment number 1
10h	WORD	ne_heap	Initial size, in bytes, of dynamic heap added to the data segment. This value is zero if no initial local heap is allocated
12h	WORD	ne_stack	Initial size, in bytes, of stack added to the data segment. This value is zero to indicate no initial stack allocation, or when SS is not equal to DS
14h	DWORD	ne_csip	Segment number:offset of CS:IP
18h	DWORD	ne_sssp	Segment number:offset of SS:SP If SS equals the automatic data segment and SP equals zero, the stack pointer is set to the top of the automatic data segment just below the additional heap area. +-----+ ! additional dynamic heap ! +-----+ ← SP ! additional stack ! +-----+ ! loaded auto data segment !% +-----+ ← DS, SS

<b>Offset</b>	<b>Size</b>	<b>Name</b>	<b>Description</b>
1Ch	WORD	ne_cseg	Number of entries in the Segment Table
1Eh	WORD	ne_cmod	Number of entries in the Module Reference Table
20h	WORD	ne_cbnrestab	Number of bytes in the Non-Resident Name Table
22h	WORD	ne_segtab	Segment Table file offset, relative to the beginning of the segmented EXE header
24h	WORD	ne_rsrctab	Resource Table file offset, relative to the beginning of the segmented EXE header
26h	WORD	ne_restab	Resident Name Table file offset, relative to the beginning of the segmented EXE header
28h	WORD	ne_modtab	Module Reference Table file offset, relative to the beginning of the segmented EXE header
2Ah	WORD	ne_imptab	Imported Names Table file offset, relative to the beginning of the segmented EXE header
2Ch	DWORD	ne_nrestab	Non-Resident Name Table offset, relative to the beginning of the file
30h	WORD	ne_cmovent	Number of movable entries in the Entry Table
32h	WORD	ne_align	Logical sector alignment shift count, log(base 2) of the segment sector size (default 9)
34h	WORD	ne_cres	Number of resource entries
36h	BYTE	ne_exetyp	Executable type, used by loader. 02h = WINDOWS
37h	BYTE	ne_flagsothers	Operating system flags
38h	WORD	???	offset to return thunks or start of gangload area
3Ah	WORD	???	offset to segment reference thunks or length of gangload area
3Ch	WORD	???	minimum code swap area size
3Eh	2 BYTES	???	expected Windows version (minor version first)

#### On-disk segment entry

<b>Offset</b>	<b>Size</b>	<b>Name</b>	<b>Description</b>
00h	WORD	ns_sector	Logical-sector offset (n byte) to the contents of the segment data, relative to the beginning of the file. Zero means no file data
02h	WORD	ns_cbseg	Length of the segment in the file, in bytes. Zero means 64K
04h	WORD	ns_flags	Flag word
06h	WORD	ns_minalloc	Minimum allocation size of the segment, in bytes. Total size of the segment. Zero means 64K

#### In-memory segment entry

<b>Offset</b>	<b>Size</b>	<b>Name</b>	<b>Description</b>
00h	WORD	ns1_sector	Logical-sector offset (n byte) to the contents of the segment data, relative to the beginning of the file. Zero means no file data
02h	WORD	ns1_cbseg	Length of the segment in the file, in bytes. Zero means 64K
04h	WORD	ns1_flags	Flag word
06h	WORD	ns1_minalloc	Minimum allocation size of the segment, in bytes. Total size of the segment. Zero means 64K
08h	WORD	ns1_handle	Selector or handle (selector - 1) of segment in memory

```
struct new_segdata {
```

```

union {
    struct {
        WORD      ns_niter;
        WORD      ns_nbytes;
        char     ns_iterdata;
    } ns_iter;
    struct {
        char     ns_data;
    } ns_noniter;
} ns_union;

};

```

## Relocation table header

<b>Offset</b>	<b>Size</b>	<b>Name</b>	<b>Description</b>
00h	WORD	nr_nreloc	???

## Relocation table entry

<b>Offset</b>	<b>Size</b>	<b>Name</b>	<b>Description</b>
00h	char	nr_stype	???
01h	char	nr_flags	???
02h	WORD	nr_soff	???
Internal fixup			
04h	char	nr_segno	???
05h	char	nr_res	???
06h	WORD	nr_entry	???
???			
04h	WORD	nr_mod	???
06h	WORD	nr_proc	???
OS Fixup			
04h	WORD	nr_ostype	???
06h	WORD	nr_osres	???
<b>Offset</b>	<b>Size</b>	<b>Name</b>	<b>Description</b>
00h	char	rs_len	???
01h	char	rs_string[1]	???
<b>Offset</b>	<b>Size</b>	<b>Name</b>	<b>Description</b>
00h	WORD	rt_id	???
02h	WORD	rt_nres	???
04h	DWORD	rt_proc	???
<b>Offset</b>	<b>Size</b>	<b>Name</b>	<b>Description</b>
00h	WORD	rn_offset	???
02h	WORD	rn_length	???
04h	WORD	rn_flags	???
06h	WORD	rn_id	???
08h	WORD	rn_handle	???
0Ah	WORD	rn_usage	???

Offset	Size	Name	Description
00h	WORD	rs_align	???
02h	struct rsrc_typeinfo	rs_typeinfo	???

From:  
<https://ftp.osfree.org/doku/> - osFree wiki



Permanent link:  
<https://ftp.osfree.org/doku/doku.php?id=en:docs:tk:formats:newexe&rev=1727355552>

Last update: **2024/09/26 12:59**