

VioGetCurPos

Bindings: [C](#), [MASM](#)

This call returns the coordinates of the cursor.

VioGetCurPos (Row, Column, VioHandle)

Row (**PUSHORT**) - output Address of the current Row position of the cursor where 0 is the top row.

Column (**PUSHORT**) - output Address of the current column position of the cursor where 0 is the leftmost column.

VioHandle (**HVIO**) - input This must be zero unless the caller is a Presentation Manager application, in which case it must be the value returned by [VioGetPs](#).

rc (**USHORT**) - return Return code descriptions are:

0	NO_ERROR
355	ERROR_VIO_MODE
436	ERROR_VIO_INVALID_HANDLE
465	ERROR_VIO_DETACHED

C bindings

```
#define INCL_VIO

USHORT rc = VioGetCurPos(Row, Column, VioHandle);

PUSHORT Row; /* Row return data */
PUSHORT Column; /* Column return data */
HVIO VioHandle; /* Vio handle */

USHORT rc; /* return code */
```

MASM bindings

```
EXTRN VioGetCurPos:FAR
INCL_VIO EQU 1

PUSH@ WORD Row ;Row return data
PUSH@ WORD Column ;Column return data
PUSH WORD VioHandle ;Vio handle
CALL VioGetCurPos

Returns WORD
```

From:

<https://ftp.osfree.org/doku/> - **osFree wiki**

Permanent link:

<https://ftp.osfree.org/doku/doku.php?id=en:ibm:prcp:vio:getcurpos>

Last update: **2016/09/15 05:03**

