

[Q]: Как в програмке под DOS отдавать тики OS/2?

[A]: Vladimir Bogoryatskih (2:5080/14.1)

Unit TimeTask;

INTERFACE

{

```
TaskRec.OS
0 : No MultiTasking
1 : Windows
2 : OS/2
3 : DESQview
4 : TopView
```

}

Type

```
TaskRec = record
  OS      : Word;
  Version : Word; {writeln('Version ',hi(Version), '.', lo(Version) );}
  Delay   : Word;
end;
```

Const

```
Task      : TaskRec = (
  OS       : 0;
  Version  : 0;
  Delay    : 100
);
```

Procedure TimeSlice; Procedure InitMulti;

IMPLEMENTATION

uses dos;

Procedure InitMulti; Assembler; Asm

```
mov  Task.OS, 0
mov  Task.Version, 0
mov  Ah, 30h
mov  Al, 01h
int  21h
cmp  Al, 20
je   @OS2
mov  Ax, 160Ah
int  2Fh
```

```
cmp Ax, 0
je @Windows
mov Ax, 1022h
mov Bx, 0000h
int 15h
cmp Bx, 0
jne @DESQview
mov Ah, 2Bh
mov Al, 01h
mov Cx, 4445h
mov Dx, 5351h
int 21h
cmp Al, $FF
jne @TopView
jmp @Fin
```

@Windows:

```
Mov Task.OS, 1
Mov Task.Version, BX
jmp @Fin
```

@OS2:

```
Mov Task.OS, 2
Mov Bh, Ah
Xor Ah, Ah
Mov Cl, 10
Div Cl
Mov Ah, Bh
Xchg Ah, Al
Mov Task.Version, AX
jmp @Fin
```

@DESQview:

```
mov Task.OS, 3
jmp @Fin
```

@TopView:

```
mov Task.OS, 4
```

@Fin: End;

Procedure TimeSlice; Assembler; Asm

```
cmp Task.OS, 0
je @Fin
cmp Task.OS, 1
```

```
je @Win_OS2
cmp Task.OS, 2
je @Win_OS2
```

@DV\_TV:

```
mov Ax, 1000h
int 15h
jmp @Fin
```

@Win\_OS2:

```
mov Ax, 1680h
int 2Fh
```

@Fin: End;

end.

From:

<https://ftp.osfree.org/doku/> - **osFree wiki**

Permanent link:

<https://ftp.osfree.org/doku/doku.php?id=ru:os2faq:os2prog:os2prog.003>

Last update: **2014/06/20 05:08**

